ATH Comfort Lift® 2.35XL

Product Images



Short Description

The ATH Comfort Lift® 2.35XL is an electrohydraulic two-post lift with a 3,500 kg capacity and a rapid-lift power unit for efficient operation. Two control units on both columns ensure maximum flexibility, each with an integrated energy set including 230 V, compressed air and 12 V. 3-stages lifting arms with double-telescopic lifting pads allow versatile vehicle pick-up from Smart to Crafter (medium). The overhead, height-adjustable crossbeam provides optimal adaptability in any workshop.

Description

Electro-hydraulic 2-post lift with quick lift unit and load-dependent lowering function

Two control units for flexible use on both columns

Energy set (230V / compressed air / 12V) on both operating units

Safety Control: Electromagnetic safety locks that automatically unlock with lifting and lowering

Safety Lock: Load-lowering control onto the safety latches

Multifunctional lifting via 3-stage lifting arms and double-telescopic lifting pads (suitable from, for example, Smart to Crafter medium wheelbase using alternative lifting points)

Overhead crossbeam with hydraulic hose and synchronization cables

Additional Information

Rated load capacity	3500 kg
Lifting height max.	2000 mm
Drive-through width	2500 mm
Overall width	3542 mm
Overall height	4280 mm
Support arms parts	3 St.
Driving power	3 kW
Lifting/Lowering time	30 | 30 s
Power supply voltage	3x 400V / C16A
Concrete strength	C 25/30 4000 x 2000 x 200 mm
Color	RAL 7016 / RAL 9005

