ATH Comfort Lift® 2.40

Product Images



Short Description

The ATH Comfort Lift® 2.40 is an electrohydraulic two-post lift with a 4,000 kg capacity and a rapid-lift power unit for efficient workshop operations. Two control units on both columns provide maximum flexibility, each equipped with an energy set including 230 V, compressed air and 12 V. 3-stages lifting arms with double-telescopic lifting pads enable versatile vehicle pick-up from Smart to Crafter (medium). The extremely low drive-over plate, only 20 mm high, reliably protects hydraulic hoses and equalization ropes.

Description

Electro-hydraulic 2-post lift with quick lift unit and load-dependent lowering function

Two control units for flexible use on both columns

Energy set (230V / compressed air / 12V) on both operating units

Safety Control: Electromagnetic safety locks that automatically unlock with lifting and lowering

Safety Lock: Load-lowering control onto the safety latches

Multifunctional lifting via 3-stage lifting arms and double-telescopic lifting pads (suitable from, for example, Smart to Crafter medium wheelbase using alternative lifting points)

Very low drive-over plate (height = 20mm) to protect hydraulic hose and synchronization cables

Additional Information

Rated load capacity	4000 kg
Lifting height max.	2500 mm
Drive-through width	2500 mm
Overall width	3542 mm
Overall height	3140 mm
Support arms parts	3 St.
Driving power	3 kW
Lifting/Lowering time	30 | 30 s
Power supply voltage	3x 400V / C16A
Concrete strength	C 25/30 4000 x 2000 x 200 mm
Color	RAL 7016 / RAL 9005

