

ATH Flex Lift® 30

Product Images



Short Description

The ATH Flex Lift® 30 is a high-quality mid rise lift with a 3,000 kg capacity and hydraulic drive, designed to require minimal maintenance. The powerful 230 V (C16A) hydraulic power unit ensures efficient daily workshop operations. With an extremely low drive-over height of approx. 105 mm, it is ideal for vehicles with low ground clearance. Mechanical synchronization via an underside cross connection and a double hydraulic lowering lock provide maximum safety—without safety locks or compressed air.

Description

High-quality and robust short-stroke lift with hydraulic drive, almost maintenance-free

Powerful hydraulic unit (230V / C16A)

Very low drive-over height of only approx. 105 mm

No electrical limit switches, protective hose over the hydraulic lines

Mechanical synchronization through cross connection and double hydraulic lines

Full lifting power from the lowest point

Emergency lowering system for lowering in the event of a power failure

Ideally suited for paint and body shops, repairs, brake and tire services

Additional Information

Rated load capacity	3000 kg
Lifting height max.	960 mm
Overall width	1952 mm
Overall height	182 mm
Driving power	2,2 kW
Lifting/Lowering time	20 20 s
Power supply voltage	230V / C16A
Color	RAL 7016 / RAL 9005
Drive-on-height	105 mm
Total platform length	1450 mm

