ATH Frame Lift® 30 FZ

Product Images



Short Description

The ATH Frame Lift® 30FZ is a high-quality double scissor lift with a 3,000 kg capacity and hydraulic drive, designed to require minimal maintenance. It is suitable for surface-mounted installation and operation and can optionally be installed flush with the floor using an in-ground kit. Synchronization control via a dual master/slave system, light barrier and double hydraulic lowering lock ensures maximum safety and precise lifting—without safety locks or compressed air.

Description

High-quality and robust double scissor lift with hydraulic drive, almost maintenance-free

Powerful hydraulic unit with load-dependent lowering valve

Very low drive-over height of only approx. 116 mm

Suitable for installation and use on the floor and optional floor-level installation (in ground kit)

Synchronization control via double master and slave systems, safety light barriers and double hydraulic lines

Full lifting power from the lowest point due to mechanical swivel system

Emergency lowering system for lowering in the event of a power failure, CE-Stop and acoustic lowering signal

Ideally suited for paint and body shops, repairs, brake and tire services

Additional Information

Rated load capacity	3000 kg
Lifting height max.	1900 mm
Overall width	2064 mm
Overall height	105 mm
Driving power	2,6 kW
Lifting/Lowering time	50 | 50 s
Power supply voltage	3x 400V / C16A
Color	RAL 7016 / RAL 9005
Drive-on-height	105 mm
Total platform length	1495 - 2030 mm

